

HTML - Attributes List

Attribute	Tag	Description
accept	<form>,<input>	List of types the server accepts, typically a file type.
accept-charset	<form>	List of supported charsets.
accesskey	Global attribute	Defines a keyboard shortcut to activate or add focus to the element.
action	<form>	The URI of a program that processes the information submitted via the form.
align	,<p>, 	Specifies the horizontal alignment of the element.
alt		Alternative text in case an image can't be displayed.
async	<script>	Indicates that the script should be executed asynchronously.
autocomplete	<form>,<input>	Indicates whether controls in this form can by default have their values automatically completed by the browser.
autoplay	<audio>,<video>	The audio or video should play as soon as possible.
autosave	<input>	Previous values should persist dropdowns of selectable values across page loads.
bgcolor	<body>	Set background color of body,This is a legacy attribute. Please use the CSS background-color property instead.
border	,<table>	Used to set border but,This is a legacy attribute. Please use the CSS border property instead.
buffered	<audio>,<video>	Contains the time range of already buffered media.
challenge	<command>,<input>	Indicates whether the element should be checked on page load.
cite	<q>	Contains a URI which points to the source of the quote or change.
class	Global attribute	Often used with CSS to style elements with common properties.
code	<applet>	This attribute gives the absolute or relative URL of the directory where applets' .class files referenced by the code attribute are stored.
color		
cols	<textarea>	Defines the number of columns in a textarea.
colspan	<td>,<th>	The colspan attribute defines the number of columns a cell should span.
content	<meta>	A value associated with http-equiv or name depending on the context.