HTML - Formatting

HTML provides the flexibility of changing the characteristics of the font such as size ,color,blod,underline etc.

Tag	Description
<font>	Set font face,size,color,etc.
<b>	Bold Text
<strong>	Important Text
<i>	Italic Text
<em>	Emphasized Text
<mark>	Marked Text
<small>	Small Text
<del>	Deleted Text
<ins>	Inserted Text
<sub>	Subscript Text
<sup>	Superscript Text

<font>

The font tag is used set color,font size,font face and erc.

Example

```
<font size="20px" color="green">Veewom</font>
```

<b>

<b> used to bold the current line character or paragraph.

Example

```
<b>Veewom</b>
```

<strong>

<strong> used to highlight the Important word in paragraph.

Example

```
<strong>Veewom</strong>
```

\<i\>

\<i\> Italic the current line or word in paragraph.

Example

```
<i>Veewom</i>
```

\<em\>

Emphasized Text

Example

```
<em>Veewom</em>
```

\<mark\>

Marked Text

Example

```
<mark>Veewom</mark>
```

\<small\>

Small Text

Example

```
<small>Veewom</small>
```

\<del\>

Deleted Text

Example

```
<del>Veewom</del>
```

<ins>

Inserted Text

Example

```
<ins>Veewom</ins>
```

<sub>

Subscript Text

Example

```
H<sub>2</sub>O
```

<sup>

Superscript Text

Example

```
C<sup>1</sup>
```

Output

C^1